A. T. M. S.

Proven Advanced Technology Solutions

AL DC-HV Portable HV Generator

by



- . 2 kV dc
- . 600 or 1200 W
- Very easy to Use

The **AL DC-HV** is well adapted for use in the field, and a typical application is the testing of Railway Catenary Voltage Detectors and their threshold settings.

Generator - One HV output adjustable in Voltage or Current by 10 turn potentiometers.

Voltage adjustment - Under 0 - 100% load, +/- 0.05% full scale. Current adjustment - Under 0 - 100% load, +/- 0.05% full scale. With respect to the supply, +/-0.05% F. S. for 10% variations for both

Protection supply by fuse, output by current limiting.

- Light weight, 15kg Smoothing & noise 0.1% RMS full scale
- Front Face Output

Flight-Case Housing with Handle. Dimensions 50 x 18 x 50 cm. Wt. 15kg Supply - 170 - 255 Vac 47 - 63 Hz Standard Ranges - (others available) Voltage - 1500, 2000 Vdc Current - 100, 200, 300, 600 mA Polarity (to be chosen on ordering)

Positive or Negative

Reversible

Floating (neither side to earth)

Insulation maintained up 110% Vout with respect to earth.

HV cables of 3m. supplied with the instrument (other lengths available)

Advanced Technology Marketing Services—26, High Street, HASLEMERE GU27 2HW

Tel - 07717763510 E-mail—sales@advantechms.com

www.advantechms.com